

EUSSEN ET AL. — 10/720,752
Attorney Docket No: 081468-0306993

- Amendment -

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (*Currently Amended*) An interferometer system for measuring displacement, along at least two directions within a three dimensional system of coordinates, of an object in a plane substantially parallel to a two dimensional plane, said interferometer system comprising:

a plane mirror interferometer system;

a differential plane mirror interferometer system; and

a beam splitter arrangement configured to split a radiation beam associated with said plane mirror interferometer system and a radiation beam associated with said differential plane mirror interferometer system into respective measuring beams and respective reference beams;

at least one measuring mirror fixedly connected to said object and comprising a plurality of measuring mirror areas; and

at least one reference mirror comprising one or more reference mirror areas that prevent said respective measuring beams and said respective reference beams from passing through said reference mirror.

2. (*Original*) The interferometer system of claim 1, wherein said beam-splitter arrangement includes a transparent body having a beam-splitting surface and a first reflector which is integrally connected to said transparent body and which has a reflective surface that extends substantially parallel to the beam splitting surface.

3. (*Currently Amended*) An interferometer system for measuring displacement along at least two directions in an XYZ system of co-ordinates, of an object in a plane substantially parallel to an XY plane, said interferometer system comprising:

EUSSEN ET AL. -- 10/720,752
Attorney Docket No: 081468-0306993

- Amendment -

at least one measuring mirror fixedly connected to said object and comprising a plurality of measuring mirror areas;

at least one reference mirror comprising ~~at least one~~ one or more reference mirror area areas that are configured to prevent radiation beams from passing through said reference mirror;

a beam generator configured to generate a plurality of radiation beams, said beam generator comprising a beam-splitter block having a beam splitting surface;

a plurality of radiation-sensitive detectors configured to convert radiation beams reflected towards said detectors into electric measuring signals;

wherein said beam splitter block is configured to split at least one first beam of said plurality of radiation beams into a first measuring beam and a first reference beam, said first reference beam only being reflected by one or more first reference mirrors located in a fixed position with respect to said beam-splitter block, said first measuring beam being reflected by a first measuring mirror area of said plurality of measuring mirror areas, and

wherein said beam splitting surface is configured to split at least one second beam of said plurality of radiation beams into a second measuring beam and a second reference beam, said second measuring beam being reflected by a second measuring mirror area of said plurality of measuring mirror areas, and said second reference beam being reflected by a first reflector that is fixedly positioned with respect to said beam-splitter block and by at least one third mirror area, which is movable with respect to said beam-splitter block.

4. *(Original)* The interferometer system of claim 3, wherein said at least one third mirror area comprises a third measuring mirror area fixed to said object.

5. *(Original)* The interferometer system of claim 3, wherein said at least one third mirror area comprises a second reflector fixed to said object and a second reference mirror area located in a fixed position with respect to said beam-splitter block, wherein said second reflector is arranged to direct said second reference beam towards said second reference mirror area.

EUSSEN ET AL. - 10/720,752
Attorney Docket No: 081468-0306993

- Amendment -

6. (Original) The interferometer system of claim 3, wherein at least one third mirror area comprises a fourth mirror area which is fixed to a second object, which is movable with respect to the beam-splitter block.

7. (Original) The interferometer system of claim 3, wherein said plurality of radiation beams comprises at least three first radiation beams occupying more than one plane and at least one second radiation beam in a position between two of said at least three first radiation beams.

8. (Currently Amended) The interferometer system of claim 3, wherein said plurality of radiation beams comprises at least three first radiation beams ~~occupying~~ arranged to occupy a polygonal volume ~~occupying more than one plane~~ and at least one second radiation beam arranged to be in a position outside ~~a polygon~~ the polygonal volume ~~formed by connecting respective first reference beams and respective first measuring beams.~~

9. (Original) The interferometer system of claim 3, wherein said beam-splitter block comprises a transparent body having a beam-splitting surface and a first reflector which is integrally connected to said transparent body and which has a reflective surface that extends substantially parallel to the beam splitting surface.

10. (Currently Amended) A lithographic apparatus comprising:
an illumination system for providing a beam of radiation;
a support structure for supporting a patterning device that serves to impart said beam of radiation with a pattern in its cross-section;
a substrate holder for holding a substrate;
a projection system for projecting said patterned beam onto a target portion of the substrate; and
an interferometer system for measuring displacement of at least one of said patterning device and said substrate, wherein said interferometer system comprises,

EUSSEN ET AL. - 10/720,752

Attorney Docket No: 081468-0306993

- Amendment -

a plane mirror interferometer system;
a differential plane mirror interferometer system; and
a beam-splitter block containing at least one beam splitter, at least one mirror, and at least one retro-reflector, such that said beam splitter block is configured to split a beam associated with said plane mirror interferometer system and a beam associated with said differential plane mirror interferometer system into respective measuring beams and respective reference beams;

at least one measuring mirror fixedly connected to said object and comprising a plurality of measuring mirror areas; and

at least one reference mirror comprising one or more reference mirror areas that prevent said respective measuring beams and said respective reference beams from passing through said reference mirror.

11. (*Currently Amended*) A lithographic apparatus comprising:
an illumination system for providing a beam of radiation;
a support structure for supporting a patterning device that serves to impart said beam of radiation with a pattern in its cross-section;
a substrate holder for holding a substrate;
a projection system for projecting said patterned beam onto a target portion of the substrate; and
an interferometer system for measuring displacement of at least one of said patterning device and said substrate, wherein said interferometer system comprises,
at least one measuring mirror fixedly connected to at least one of said patterning device and said substrate, said at least one measuring mirror comprising a plurality of measuring mirror areas;
at least one reference mirror comprising ~~at least one~~ one or more reference mirror ~~area~~ areas that are configured to prevent beams from passing through said reference mirror;
a beam generator configured to generate a plurality of beams, said beam generator comprising a beam-splitter block having a beam splitting surface; and

EUSSEN ET AL. -- 10/720,752
Attorney Docket No: 081463-0306993

- Amendment -

a plurality of radiation-sensitive detectors configured to convert radiation beams reflected towards said detectors into electric measuring signals,

wherein said beam splitter block is configured to split at least one first beam of said plurality of radiation beams into a first measuring beam and a first reference beam, said first reference beam only being reflected by one or more first reference mirrors located in a fixed position with respect to said beam-splitter block, said first measuring beam being reflected by a first measuring mirror area of said plurality of measuring mirror areas, and

wherein said beam splitting surface is configured to split at least one second beam of said plurality of radiation beams into a second measuring beam and a second reference beam, said second measuring beam being reflected by a second measuring mirror area of said plurality of measuring mirror areas, and said second reference beam being reflected by a first reflector that is fixedly positioned with respect to said beam-splitter block and by at least one third mirror area, which is movable with respect to said beam-splitter block.

12. *(Currently Amended)* The ~~interferometer-system~~ lithographic apparatus of claim 11, wherein said at least one third mirror area comprises a third measuring mirror area fixed to said object.

13. *(Currently Amended)* The ~~interferometer-system~~ lithographic apparatus of claim 11, wherein said at least one third mirror area comprises a second reflector fixed to said object and a second reference mirror area located in a fixed position with respect to said beam-splitter block, wherein said second reflector is arranged to direct said second reference beam towards said second reference mirror area.

14. *(Currently Amended)* The ~~interferometer-system~~ lithographic apparatus of claim 11, wherein at least one third mirror area comprises a fourth mirror area which is fixed to a second object, which is movable with respect to the beam-splitter block.

EUSSEN ET AL. - 10/720,752
Attorney Docket No: 081468-0306993

- Amendment -

15. (*Currently Amended*) The ~~interferometer-system~~ lithographic apparatus of claim 11, wherein said plurality of radiation beams comprises at least ~~three~~ first three radiation beams occupying more than one plane and at least one ~~second~~ second radiation second radiation beam in a position between two of said at least three first radiation beams.

16. (*Currently Amended*) The ~~interferometer-system~~ lithographic apparatus of claim 11, wherein said plurality of radiation beams comprises at least three first radiation beams ~~occupying~~ arranged to occupy a polygonal volume ~~occupying more than one plane~~ and at least one second radiation beam arranged to be in a position outside a ~~polygon~~ the polygonal volume formed by connecting respective first reference beams and respective first measuring beams.

17. (*Currently Amended*) The ~~interferometer-system~~ lithographic apparatus of claim 11, wherein said beam-splitter block comprises a transparent body having a beam-splitting surface and a first reflector which is integrally connected to said transparent body and which has a reflective surface that extends substantially parallel to the beam splitting surface.

18. (*Currently Amended*) A device manufacturing method comprising:
providing a substrate;
providing a beam of radiation using an illumination system;
using patterning device to impart beam of radiation with a pattern in its cross-section; and
projecting said patterned beam of radiation onto a target portion of the substrate,
wherein a position of at least one of said patterning device and said substrate is determined by an interferometer system, said interferometer system comprising,
at least one measuring mirror fixedly connected to at least one of said patterning device and said substrate, said at least one measuring mirror comprising a plurality of measuring mirror areas,

EUSSEN ET AL. — 10/720,752
Attorney Docket No: 081468-0306993

- Amendment -

at least one reference mirror comprising ~~at least one~~ one or more reference mirror ~~area~~ areas that are configured to prevent beams from passing through said reference mirror,

a beam generator configured to generate a plurality of beams, said beam generator comprising a beam-splitter block having a beam splitting surface, and

a plurality of radiation-sensitive detectors configured to convert said beams which are reflected towards said detectors into electric measuring signals,

wherein said beam splitter block is configured to split at least one first beam of said plurality of beams into a first measuring beam and a first reference beam, said first reference beam only being reflected by one or more first reference mirrors located in a fixed position with respect to said beam-splitter block, said first measuring beam being reflected by a first measuring mirror area of said plurality of measuring mirror areas, and

wherein said beam splitting surface is configured to split at least one second beam of said plurality of beams into a second measuring beam and a second reference beam, said second measuring beam being reflected by a second measuring mirror area of said plurality of measuring mirror areas, and said second reference beam being reflected by a first reflector that is fixedly positioned with respect to said beam-splitter block and by at least one third mirror area, which is movable with respect to said beam-splitter block.

19. *(Original)* The method of claim 18, wherein said at least one third mirror area of said interferometer system comprises a third measuring mirror area fixed to said object.

20. *(Original)* The method of claim 18, wherein said at least one third mirror area of said interferometer system comprises a second reflector fixed to said object and a second reference mirror area located in a fixed position with respect to said beam-splitter block, wherein said second reflector is arranged to direct said second reference beam towards said second reference mirror area.

EUSSEN ET AL. -- 10/720,752
Attorney Docket No: 081468-0306993

- Amendment -

21. *(Original)* The method of claim 18, wherein said at least one third mirror area of said interferometer system comprises a fourth mirror area which is fixed to a second object which is movable with respect to the beam-splitter, block.

22. *(Original)* The method of claim 18, wherein said plurality of beams of said interferometer system comprises at least three first radiation beams occupying more than one plane and at least one second radiation beam in a position between two of said at least three first radiation beams.

23. *(Currently Amended)* The method of claim 18, wherein said plurality of radiation beams comprises at least three first radiation beams ~~occupying~~ arranged to occupy a polygonal volume ~~occupying more than one plane~~ and at least one second radiation beam arranged to be in a position outside a ~~polygon~~ the polygonal volume ~~formed by connecting respective first reference beams and respective first measuring beams.~~

24. *(Original)* The method of claim 18, wherein said beam-splitter block of said interferometer system comprises a transparent body having a beam-splitting surface and a first reflector which is integrally connected to said transparent body and which has a reflective surface that extends substantially parallel to the beam splitting surface.